



## Airfix D-E-B 16 bar (g)

**Application**

Expansion vessel for potable water or sprinkler installations.

**Advantages**

- ◆ The composition of the membranes has been made for this range in such a way that there will be no variation in smell, colour or taste.
- ◆ The inside of the Airfix vessel has a special coating which prevents oxidation.
- ◆ Replaceable bladder.
- ◆ CE approved according to EU Pressure Equipment Directive 97/23/EC.
- ◆ WRAS and ACS approved.

**Product information**

- ◆ With single threaded steel connection (no flow-through function).
- ◆ Without membrane-rupture sensor.
- ◆ Max. working temperature: 70 °C (343 K).
- ◆ Material quality:

A181 class 60	: ASTM
RSt37.2/C22.3	: DIN
1503-221-410	: BS
S235JRG2 EN 10250/2	: EN/ISO
P245N EN10222/2	: EN/ISO

**Technical information**

Type	Volume (litre)	Dimensions Ø (mm)	Dimensions Height (mm)	Connection (F)	Weight (kg)		16.0 bar (g) Order Code
Airfix D-E-B 50	50	450	839	1 1/2"	45		1 14703
Airfix D-E-B 80	80	450	1019	1 1/2"	53		1 14803
Airfix D-E-B 120	120	450	1274	1 1/2"	64		1 14815
Airfix D-E-B 180	180	550	1238	1 1/2"	90		1 14821
Airfix D-E-B 240	240	550	1498	1 1/2"	107		1 14827
Airfix D-E-B 300	300	550	1838	1 1/2"	128		1 14833
Airfix D-E-B 600	600	750	1843	2"	241		1 14863
Airfix D-E-B 800	800	750	2233	2"	285		1 14883
Airfix D-E-B 1000	1000	750	2733	2"	339		1 14913
Airfix D-E-B 1600	1600	1000	2682	2 1/2"	578		1 14919
Airfix D-E-B 2000	2000	1200	2425	2 1/2"	725		1 14923
Airfix D-E-B 3000	3000	1200	3325	2 1/2"	982		1 14933